

Building the access pointers to a computation environment[†]

V.E.Wolfengagen

Vorotnikovsky per., 7, bld. 4

Institute for Contemporary Education “JurInfoR-MSU”

Moscow, 103006, Russia

vew@jmsuice.msk.ru

Abstract

A common object technique equipped with the categorical and computational styles is briefly outlined. An object is evaluated by embedding in a host computational environment which is the domain-ranged structure. An embedded object is accessed by the pointers generated within the host system. To assist with an easy extract the result of the evaluation a pre-embedded object is generated. It is observed as the decomposition into substitutional part and access function part which are generated during the object evaluation.

1 Introduction

Recent issues in a data modeling area tend to attract some general algebraic ideas. The most influent to the target data model are the properties of the database domains and their interconnections.

Some useful observations concerning the mappings between the *relational database* domains [IP94] result in the solutions to integrate a database scheme. But the difficulties were observed when the *type* considerations occurs: the first-order data model becomes overloaded with the complicated and intuitively unreasonable mappings, especially when attempts to use a *category* theory are done.

The attempts to apply the same ideas for a *conceptual modeling* [LH96] are not yet advanced to cover the known effects and models. A gap between the pure reasoning with the objects in a category-style manner (the maps and domains have the similar status) and the realistic data models is indicated every time (see, e.g., [HLF96]) when the researcher put the database concepts together. Nevertheless, the feeling of a category theory usefulness is growing with the rate of accumulating the practical experience in a field [Jac91].

The *semantics* of database is heavy based on the evaluation of the expressions [BSW94]. The success of the approach is also estimated by the simplicity and intuitive transparency whenever the maps between domains are involved. Information system engineering [JD93] extremely needs to apply the theoretically balanced data models with the higher-order structures.

[†]This research is supported by the Russian Foundation for Basic Research (project 96-01-01923)

Proceedings of the First East-European Symposium on Advances in Databases and Information Systems (AD-BIS'97). St.-Petersburg, September 2–5, 1997.
St.-Pb.: St.-Petersburg University, 1997.

The observations show the concepts and notions shared by the distinct approaches and the theories. The importance of extracting all the useful feature from the notions of *function* and *type* are well understood. Here we will try to rearrange and put together some important ideas concerning the evaluation of expressions. The most of the attention is paid to *environment* of the evaluation to suit it with the common database models. An environment is assumed to consist of the *products* of the domains. Thus, the obvious way to get an access to its partitions is to evaluate the *projections*, each of them being type according to the positions of the counterparts. This intuitively means, the *pointers* to an environment are to be generated. Some unexpected features arise wherever the *encapsulation* of objects is used relatively the environment prescribed.

To cover the notion in use the most of attention is paid to interrelations and correspondences between *types*, *functions* and *environment* of evaluation. The *language* is left out of this paper scope, and model theoretic aspects are attracted. The style of reasoning in a category is used along with the equational solutions.

Section 2 covers the minimal amount of a type theory to put the necessary accents. The projections are used almost in a traditional sense. The operation $\hat{}$ gives a kind of suit to shift around the variables. In addition, the correspondence between the projections and the *identity maps* brings in a theory the intuitive ground.

An access to values coupled in environment is discussed in section 3. The main topics are generation of the *access pointers* and the *encapsulation* of the objects. The commutative diagram techniques is applied to establish the most important equation. The reasons and solutions are based on the possibilities of the *citation*. An atomic case is covered by Lemma 3.1. Its generalization leads to the Theorem 3.1 whenever the function constant is applied to an argument. To pass an *actual parameter* the *closure* is generated.

2 A theory of types

A variety of possible theories of types has been developed with different purposes and with distinct mathematical or logical ideas in use. A category theory gives one of the theories.

To establish a universe of discourse for types we need some kind of *primitive frame*. Usually we start with a set of *generic* types and generate the *derived* types applying some building principles. In a pure category theory we are not given neither building principles nor clear understanding of making new types from old. Entering a category theory we observe the relations between types which hold whenever corresponding mapping statement

$$f : Env \rightarrow D_y \quad (1)$$

obtains (here: Env and D_y are domains).

The way of reading the *mapping statement* depends on intuitive reasons. Whenever we apply to category theory, a mapping statement is supposed being taken as a statement with one-place functions and operation ‘ $\circ$ ’ of composition with one-place functions. Thus, practical reasons concern the multi-place functions to increase their arity.

The solutions to bring composition with multi-place functions (see, e.g., [Sza78]) are known but give no real suit.

The easier way is to assume that the category has *cartesian products* and to select the particular representatives of the product domains. In particular, the cartesian power D^n for every $n \geq 0$ gives n -ary functions as maps

$$f : D^n \rightarrow D_y. \quad (2)$$

2.1 A description of products

2.1.1 Empty product.

To make a description of products we bring in the product and start with the assumption that a category has a special domain $\mathcal{O}$ as the empty product:

$$D_y^0 = D_x^0 = \mathcal{O}, \quad (3)$$

and for every domain D a special map:

$$0_D : D \rightarrow \mathcal{O} \quad (4)$$

From an intuitive reason the domain $\mathcal{O}$ has one element, and map 0_D is unique, i.e. whenever $f : D \rightarrow \mathcal{O}$ then $f = 0_D$.

2.1.2 A theory of tuples and multi-ary maps.

This kind of a theory is based on the *products*. Concerning *binary products* we have for arbitrary two domains D_x and D_y a special choice of a domain $D_x \times D_y$, and, more generally,

$$D^{n+1} = D^n \times D, \quad n > 0.$$

A product is equipped with the special maps

$$\begin{aligned} Fst & : D_y \times D_x \rightarrow D_y, \\ Snd & : D_y \times D_x \rightarrow D_x, \end{aligned}$$

which are the *projections*. As usually, mere existence of maps Fst and Snd does not characterize $D_y \times D_x$ as a product. In addition we assume that there is a chosen *pairing operation* $\langle f, g \rangle$ on maps such that types are assigned by the rule:

$$\frac{f : Env \rightarrow D_y, \quad g : Env \rightarrow D_x}{\langle f, g \rangle : Env \rightarrow D_y \times D_x}$$

The additional property of Fst , Snd and $\langle \cdot, \cdot \rangle$ under *composition* is assumed:

$$\begin{aligned} Fst \circ \langle f, g \rangle &= f, \\ Snd \circ \langle f, g \rangle &= g, \\ \langle Fst \circ h, Snd \circ h \rangle &= h, \end{aligned}$$

where f, g are typed as above, and

$$h : Env \rightarrow D_y \times D_x$$

One-to-one correspondence. It means that there is a one-one correspondence between the pairs of maps f, g and the map h into the product.

2.1.3 A theory of functions.

A category usually gives a ‘local’ universe of *selected* functions. In case of *arbitrary* functions we need the *functional spaces* as explicit domains in the category.

Given D_x and D_y we want to form $(D_x \rightarrow D_y)$ as a domain in its own right. After adopting the above, the functional space does contain the various maps.

Whenever we have an element f from $(D_x \rightarrow D_y)$ and the element x from D_x we need to establish the map that will apply element f to element x giving rise to the *value* of function f :

$$\varepsilon : [f, x] \mapsto f(x)$$

This *evaluation* map ε is typed as

$$\varepsilon : (D_x \rightarrow D'_y) \times D_x \rightarrow D'_y$$

In addition there has to be a map for shifting around *variables*. Suppose

$$g : Env \times D_x \rightarrow D'_y$$

is a map with two arguments. In an evaluation

$$g([i, x])$$

we can think of holding i constant and regarding $g([i, x])$ as a function of x . We need a name for this function and for correspondence with possible values of x :

$$\hat{g} : Env \rightarrow (D_x \rightarrow D'_y)$$

so that the function we are thinking of - given x - was

$$\hat{g}(i)(x)$$

Map k is one-to-one corresponded to g . All this function value notation is not categorical notation. Nevertheless we are to say that there is a one-one correspondence via $\hat{\cdot}$ between maps $g : Env \times D_x \rightarrow D_y$ and maps $k : Env \rightarrow (D_x \rightarrow D_y)$.

This correspondence comes down to the following two equations:

$$\begin{aligned} \varepsilon \circ (\hat{g} \times id_{D_x}) &= g, \\ \varepsilon \circ (k \times id_{D_x}) &= k, \end{aligned}$$

where $(\cdot \times \cdot)$ means a *functor product*, or, in the neutral to domains form,

$$\begin{aligned} \varepsilon \circ \langle \hat{g} \circ Fst, Snd \rangle &= g, \\ \varepsilon \circ \langle k \circ Fst, Snd \rangle &= k, \end{aligned}$$

where $\langle \cdot \circ Fst, Snd \rangle$ is the same as $(\cdot \times id_{D_x})$.

The notation is now wholly categorical and not so suitable. The more sense is added by the language of *functors*.

2.1.4 A system of types within cartesian closed category

Now we give a brief sketch of viewing the cartesian closed category (c.c.c.) as a system of types.

Theory of functions. Each c.c.c. represents a *theory of functions*.

Maps. The *maps* in the category are certain special functions that are used to express the relations between the types (the domains of the category).

Products. In order to be able to deal with multi-ary functions, we assume we can form and analyze *products*.

Function spaces. In order to be able to work with transformations of arbitrary functions (arbitrary within the theory) we assume we can form *function spaces*. Note, that the *higher* types enter the theory, e.g., as the sequence of domains:

$$D, (D \rightarrow D), ((D \rightarrow D) \rightarrow D), \dots$$

Operations ε and $\hat{\cdot}$. To be able really to view these domains as function spaces, certain operations, ε and $\hat{\cdot}$, with characteristic equations have to be laid down.

Cartesian closed category. C.c.c is a theory of functions, and the higher type functions are included. Hence, the theory of c.c.c's is the *theory of types*. It is only one such theory.

'Bigger' theories. 'Bigger' theories could be obtained by demanding more types, e.g., by axiomatizing *coproducts* (disjoint sums) and $D_x + D_y$

Type $[]$. We could throw in type $[]$ of propositions so that higher types like $(D^n \rightarrow [])$ correspond to n -ary predicates.

3 Environment and an access to values

To build the typed language we need to think of the values of the variables. The values of the variables are available via *access functions* from an environment Env . The representation of an environment is given by the domains $D_y, D_x, \dots$ which are ranges of possible values of $y, x, \dots$. The domains D_y, D_x give the *explicit* part of an environment Env , and its *implicit* rest E , not be detailed for current consideration, is separated from D_y, D_x :

$$Env = (E \times D_y) \times D_x$$

3.1 Updating an environment

Whenever we want to *update* Env the restriction is imposed to its counterparts:

$$Env = Implicite_part \times Explicite_part,$$

e.g.,

$$Env = E \times D_x$$

with ' E ' for implicit part and ' D_x ' for explicit part.

In fact, within Env we have an 'old' value of x which ranges $D_{x,Old}$, and E which does not depend on x . The description of updating an environment Env has to include both its explicit part D_x and implicit rest E . An outline of *updating process* is given below.

Step 1: Building the old environment. To combine Env_{Old} we construe the product

$$Env_{Old} = E \times D_{x,Old}.$$

Step 2: Bringing in a range of values. The product of Env_{Old} and D_x is generated as

$$Env_{Old} \times D_x = (E \times D_{x,Old}) \times D_x.$$

Step 3: Establishing an $Update_x$ -function. The An $Update_x$ function is established to enable the transformation from Env_{Old} to Env_{New} :

$$Update_x : (E \times D_{x,Old}) \times D_x \rightarrow E \times D_{x,New},$$

or,

$$Update_x : Env_{Old} \times D_x \rightarrow Env_{New}.$$

At this stage we are to compare the properties of the domains $D_x, D_{x,Old}, D_{x,New}$:

- (1) D_x is an unrestricted range for free variable x ;
- (2) $D_{x,Old}$ is some *existing* (i.e., *before* evaluation) restriction of D_x ;
- (3) $D_{x,New}$ differs from $D_{x,Old}$ exclusively in a point x .

All of this could be implemented in a particular kind of $Update_x$, which would be referred as *substitution*, or $Subst_x$:

$$Subst_x : Env_{Old} \times D_x \rightarrow Env_{New}.$$

The description of its behavior by the elements gives the following:

$$Subst_x : [i, d] \mapsto i_{(d/x)},$$

where $d \in D_x, i \in Env_{Old}$, and $i_{(d/x)} \in Env_{New}$. [Here: the new instance $i_{(d/x)}$ of environment is the same as its old instance i *excepting* the point x , which is replaced by d .]

One could imagine that there is a pointer from ' x ' to its possible values ' d '.

3.2 Viewing $Subst_x$ as a pointer

Now we discuss the possibility to construe a pointer to the partitions of an environment. At first, we would try the equation

$$\begin{aligned} Subst_x &= Fst \times id_{D_x} \\ &= \langle Fst \circ Fst, id_{D_x} \circ Snd \rangle \\ &= \langle Fst \circ Fst, Snd \rangle, \end{aligned}$$

where $Fst \times id_{D_x}$ is a *functor product*, $\langle Fst \circ Fst, Snd \rangle$ its linear notation, and

$$Subst_x : Env_{Old} \times D_x \rightarrow Env_{New}$$

for $Env = (E \times D_y) \times D_x$.

The functor product when being applied to *ordered pair* generates an access separately to the *first* and to the *second* its members. This feature makes it possible to bring in the following maps as the pointers to the partitions of the environment.

Pointer to the part independent on ' x '. This is a composition of Fst 's which ranges the product $E \times D_y$, i.e. and implicit – and independent, – part of the environment:

$$Fst \circ Fst : Env_{Old} \times D_x \rightarrow E \times D_y$$

Pointer to the part of new values for ' x '. This is a second projection Snd which ranges over the desired domain D_x :

$$Snd : Env_{Old} \times D_x \rightarrow D_{x,New}$$

Coupling the new environment. Now we generate an access to the new environment. Taking into account the pointers for both the partitions, we need to construe their *couple* to obtain the pointer to the new environment:

$$\langle Fst \circ Fst, Snd \rangle : Env_{Old} \times D_x \rightarrow Env_{New}$$

Getting started with a new environment

$$Env_{New} = (E \times D_y) \times D_{x,New},$$

we can evaluate the *arbitrary functions*. The process of extracting the pointers to $D_y, D_{x,New}$ and generating the values from D'_y whenever $D_y = (D'_y)^{D_x} (= D'_y \rightarrow D_x)$, i.e. for the *function space* D_y , comes down to the following steps.




Figure 1: Encapsulation of a constant a (Notations and explanation: i is an instance of environment Env , thus $i \in Env$; $i_{(a/a)}$ means the instance of environment which captured the constant a , also means the substitution of domain for a by a ; a closure $1_{\{a\}}$ (identity map as a canonical evaluation) for the evaluated constant is generated; whenever a closure is not the identity map then the constant is not canonically evaluated. As may be shown, the map g is equal to $1_{\{a\}} \circ Snd$.)

Step 1: Access to D_y . We take the first partition (Fst) of Env_{New} and after that construe the pointer to its second (Snd) partition:

$$Snd \circ Fst : Env_{New} \rightarrow D_y$$

Step 2: Access to $D_{x,New}$. An effect of applying Snd to Env_{New} gives the pointer

$$Snd : Env_{New} \rightarrow D_{x,New}$$

Step 3: Coupling an access to D'_y for $D_y = (D'_y)^{D_x}$ by ε . We take the subpartitions of Env_{New} as above and restore the pointer:

$$< Snd \circ Fst, Snd > : Env_{New} \rightarrow ((D'_y)^{D_x} \times D_{x,New})$$

taking in mind that $\varepsilon : (D'_y)^{D_x} \times D_{x,New} \rightarrow D'_y$.

Now we are able to take a function f from $(D'_y)^{D_x}$ and the argument d from $D_{x,New}$ and apply f to d using ε . Thus, the equation $\varepsilon[f, d] = f(d)$ is valid giving rise to the values $f(d)$ from D'_y

3.3 Encapsulation of an object

In particular, an evaluation process may result in capturing the object being evaluated by an environment.

Lemma 3.1 (Citation) For any given environment $Env = (E \times D_y) \times D_x$ and the domain $D_y = (D'_y)^{D_x}$ the constant $c \in D_x$ and the function constant $f \in D_y$ are described by the maps $(1_{\{c\}} \circ Snd)$ and $(f \circ Snd)$ respectively.

Proof. For any given instance $i \in Env$, e.g., $i = [[e, y], x]$ whenever $x, d \in D_x, y, f \in D_y$ then:

- (1) $(1_{\{c\}} \circ Snd) i c = (1_{\{c\}} \circ Snd)[i, c] = 1_{\{c\}} c = c$.
- (2) $(f \circ Snd) i d = (f \circ Snd)[i, d] = f(d)$.

Thus, this proof is straightforward and elementary.

Canonical evaluation of a constant is according the commutative diagram in Figure 1. The reasons are as follows. Let i be an instance of environment Env , thus, $i \in Env$. Each occurrence of ' a ' canonically is replaced by the same ' a ', i.e. $i_{(a/a)}$ means the instance of environment which captured the constant a , also means the substitution of domain for a by a . We need a closure to trigger the evaluation process, and $1_{\{a\}}$ (identity map as a canonical evaluation) for the evaluated constant is generated. Roughly speaking, this identity map evaluates a constant and whenever a closure is not the identity map then the constant is not canonically evaluated.

Now we describe the evolution of an environment when encapsulation of the constant occurs. The environment in Figure 2 is treated as the cartesian product of the range domains. The notations




Figure 2: Environment of encapsulation (Notations and explanation: D_a is a range of a -compatible objects, i.e. those with the same type; for simplicity we assume $D_a = \{a\}$; singleton $\{a\}$ is the encapsulated constant. The map $Encapsulate_a$ builds a renewed environment by setting up the product of implicit partition of the environment with the singleton $\{a\}$.)

naturally reflects the ranges, and D_a is a range of a -compatible objects, i.e. those with the same type. For simplicity we assume $D_a = \{a\}$, and this singleton $\{a\}$ is the encapsulated constant. The map $Encapsulate_a$ builds a renewed environment by setting up the product of implicit partition of the environment with the singleton $\{a\}$.

3.4 Building a pointer to values

3.4.1 Evaluation of a variable

For single free variable the element-wise reasons for the evaluation are described by the commutative diagram in Figure 3. To read this diagram we use the additional notations: $d \in D_x$ for an element being substituted; $1_{D_x} : D_x \rightarrow D_x$ for an identity map.

We try to 'solve' this diagram relatively g and $Subst_x$.

Solution for g . For every $i \in Env$ the maps

$$\begin{array}{ll} \hat{g}(i) : D_x \rightarrow D_x; & \hat{g}(i) : d \mapsto d, \\ \hat{g} : Env \rightarrow (D_x \rightarrow D_x); & \hat{g} : i \mapsto 1_{D_x}, \\ g : Env \times D_x \rightarrow D_x; & g : [i, d] \mapsto d \end{array}$$

are valid, hence the following is a 'solution':

$$\boxed{g = Snd}$$

The value of a free variable is represented by an identity map. Note that this diagram corresponds to some idea of closure: free variable is supposed to be closed under the environment of its evaluation.

Solution for $Subst_x$. For every $i = [e, x]$ from 'old' environment the map $Subst_x$ gives $[e, d]$ as an instance of 'new' environment:

$$Subst_x : [[e, x], d] \mapsto [e, d],$$

hence,

$$\boxed{Subst_x = < Fst \circ Fst, Snd >}$$

Therefore, the 'solution' of diagram in Figure 3 for g and $Subst_x$ in case we evaluate a single free variable is given by diagrams in Figure 4 and in Figure 5.

3.4.2 Evaluation of a constant function

Evaluation of a constant function gives the most typical sample to encapsulate the object of general nature. To observe the effects we describe an applying of the constant function to the argument. All the counterparts - both function and argument, - from the category theory view are the objects.

The environment is changed whenever the application of the function f to the argument x occurs, i.e. the triggering event is




Figure 3: Substitution of a variable (Notations and explanation: $d \in D_x$ an element being substituted; $1_{D_x} : D_x \rightarrow D_x$ is an identity map. In evaluation of a variable the most important is its substitutional property. The closure for a variable is generated resulting in its image 1_{D_x} .)




Figure 4: Pointers for a variable (Notations and explanation: an environment $i_{(d/x)}$ is the same as environment i excepted point x which is replaced by d . In case of evaluating a single free variable, map ' g ' from the diagram in Figure 3 is to be replaced by the pointer Snd .)




Figure 5: Partitioning an environment Env (Explanation: this diagram is expansion of the element-wise commutative diagram in Figure 4 to the corresponding domains.)




Figure 6: Evaluation of a constant function (Explanation: this commutative diagram reflects a natural idea of the function constant, i.e. the evaluated map does not depend on an environment. A diagram to evaluate its argument variable is similar to diagram in Figure 3. The diagram (a) is a commutative-style description of evaluating the argument of the function f . The diagram (b) describes the intuitive reasons to observe f as a function constant which results in $f(d)$, the value of f in a point d . The diagram (c) determines f as the valid map. An assembling diagrams (a), (b), and (c) gives the commutative diagram (abc). All the diagrams contain the parameters g_f, g_d which are to satisfy the commutative law. Thus, the 'solution' of diagram (abc), if exists, relatively g_f, g_d generates the pointers to access an environment.)

(fx), or similarly, $f(x)$. In the environment an evaluation is triggered whenever the value of argument ' d ' is passed to ' x '.

The following Theorem 3.1 reflects the computational ideas in use.

Theorem 3.1 (Citation of the function) (1) The equation

$$f \circ (\varepsilon \circ \langle \hat{g}_d \times id_{D_x} \rangle) = \varepsilon \circ \langle \hat{g}_f \times id_{D_x} \rangle$$

describes the object f as a functional constant parameterized by g_d and g_f .

(2) The equation in (1) has the solution

$$\begin{aligned} g_d &= 1_{D_x} \circ Snd, \\ g_f &= f \circ Snd, \end{aligned}$$

thus, the pointers to an environment are generated.

Proof. (1) The equation above is commented as follows:

Left part: $f \circ (\varepsilon \circ \langle \hat{g}_d \times id_{D_x} \rangle)$ eval of 'x' within env 'i' when actual parameter 'd' is passed to argument 'x'	Right part: $\varepsilon \circ \langle \hat{g}_f \times id_{D_x} \rangle$ eval of 'fx' within env 'i' when actual parameter 'd' is passed to argument 'x'
---	---

The premise of the sentence is described by the commutative diagrams (a), (b), and (c) in Figure 6. The equation is valid due to the existence of commutative diagram (abc), thus the conclusion is valid.

(2) The existence of the pointers is due to Lemma 3.1. Hence, the commutative diagram in Figure 7 gives the needed pointers.




Figure 7: Pointers to access the environment with a constant function (Explanation: this commutative diagram gives one of the possible solutions of the diagrams in Figure 6 relatively the parameters g_f and g_d . Thus, the parameter g_d is replaced by $1_{D_x} \circ Snd$, g_d by $(1_{D_x} \circ Snd)$, g_f by $f \circ Snd$, and g_f by $(f \circ Snd)$.)

4 Conclusions

A common object technique equipped with the categorical and computational styles is outlined. As was shown, an object can be represented by embedding in a host computational environment. An embedded object is accessed by the laws of the host system. A pre-embedded object is observed as the decomposition into substitutional part and access function part which are generated during the object evaluation. They assist to easy extract of the result.

Acknowledgements

The author is indebted to Institute for Contemporary Education "JurInfoR-MSU" for stimulating the research.

References

- [AGN95] A. Asperti, C. Giovannetti, and A. Naletto. The Bologna optimal higher-order machine. Technical Report UBLCS-95-9, University of Bologna, Department of Computer Science, March 1995.
- [BSW94] K. Baclawski, D. Simovici, and W. White. A categorical approach to database semantics. *Mathematical Structures in Computer Science*, 4:147–183, 1994.
- [Cor89] T. Corbi. Program understanding: Challenge for the 1990s. *IBM Systems Journal*, 28(2):294–306, 1989.
- [CW85] L. Cardelli and P. Wegner. On understanding types, data abstractions, and polymorphism. *Computing Surveys*, 17(4), December 1985.
- [EWH85] R. Elmasri, J. Weeldreyer, and A. Hevner. The category concept: An extension to the entity-relationship model. *Data & Knowledge Engineering*, 1:75–116, 1985.
- [Gil87] J. P. Gilbert. *Polyview: An Object Oriented Data Model for Supporting Multiple User Views*. PhD thesis, University of California, 1987.
- [HLF96] A.H.M. ter Hofstede, E. Lippe, and P.J.M. Frederiks. Conceptual Data Modeling from a Categorical Perspective. *The Computer Journal*, 39(3):215–231, August 1996.

- [HLW95] A.H.M. ter Hofstede, E. Lippe, and Th.P. van der Weide. A Categorical Framework for Conceptual Data Modeling: Definition, Application, and Implementation. Technical Report CSI-R9512, Computing Science Institute, University of Nijmegen, Nijmegen, The Netherlands, November 1995.
- [Hoa89] C.A.R. Hoare. Notes on an Approach to Category Theory for Computer Scientists. In M. Broy, editor, *Constructive Methods in Computing Science*, volume 55 of *NATO Advanced Science Institute Series*, pages 245–305. Springer-Verlag, 1989.
- [IP94] A. Islam and W. Phoa. Category Models of Relational Databases I: Fibrational Formulation, Schema Integration. In M. Hagiya and J.C. Mitchell, editors, *Theoretical Aspects of Computer Software, International Symposium TACS'94*, volume 789 of *Lecture Notes in Computer Science*, pages 618–641, Sendai, Japan, April 1994. Springer-Verlag.
- [Jac91] B.P.F. Jacobs. *Categorical type theory*. PhD thesis, University of Nijmegen, Nijmegen, The Netherlands, 1991.
- [JD93] M. Johnson and C.N.G. Dampney. Category theory and information system engineering. In *Proceedings of the Third International Conference AMAST'93 on Algebraic Methodology and Software Technology, Workshops in Computing*, pages 95–103, University of Twente, Enschede, The Netherlands, June 1993. Springer-Verlag.
- [KC93] S.-K. Kim and S. Chakravarthy. An interpretation and implementation of temporal databases with two-dimensional time. Technical Report UF-CIS-TR-93-030, University of Florida, Department of Computer Science, September 1993.
- [LH96] E. Lippe and A.H.M. ter Hofstede. A Category Theory Approach to Conceptual Data Modeling. *RAIRO Theoretical Informatics and Applications*, 30(1):31–79, 1996.
- [Oli94] A. Oliart. An algorithm for inferring quasi-static types. Technical report, 111 Cummington St. Boston. MA 02215 USA, December 1994.
- [Sza78] M.E. Szabo. *Algebra of proofs*. North-Holland, 1978.
- [Tui94] C. Tuijn. *Data Modeling from a Categorical Perspective*. PhD thesis, University of Antwerp, Antwerp, Belgium, 1994.